

SPECIFICATION FOR LCD MODULE

Customer : _____
CustomerP/N _____
Model No. : **B22C40290N-01-C**
Version : **V03**
Date : **2025-08-19**

Final Approval by Customer

LCM Machinery OK ☐	Checked By	
LCM Display OK ☐	Checked By	
LCM NG ☐ LCM OK ☐	Approved By	

ShenZhen BELIJ Confirmed :

DESIGN	CHECK	APPROVAL

Add: 3/F,C Building.zhongnangang.Industrial city,sili Road.guanlan Town,shenzhen city

Http: www.szbelij.com

Tel: (0755)29062552

Fax: (0755)29062550

PC: 518000

LIST OF CONTENTS

No.	CONTENTS	PAGE
1	REVISION HISTORY	
2	GENERAL INFORMATION	
3	ABSOLUTE MAXIMUM RATINGS	
4	DC ELECTRICAL CHARACTERISTICS	
5	TIMING CHARACTERISTICS	
6	RESET TIMING	
7	EXTERNAL DIMENSIONS	
8	INTERFACE SIGNALS	
9	ELECTRO-OPTICAL CHARACTERISTICS	
10	RELIABILITY TEST CONDITIONS	
11	INSPECTION CRITERION	
12	PRECAUTINGS FOR USING LCD MODULES	

1 REVISION HISTORY

The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD.

Version	Date	Description	Revised By
V00	2022-09-07	First Issued	FLQ
V01	2022-11-07	LCD 铺铜区域去掉,增加二维码, 背光贴两条硅胶垫;TP 电磁膜去掉,增加双层保护膜 , 更改 TP 排线泡棉, 背胶尺寸,铁框增加 LCD/TP 对位线.	FLQ
V02	2024-04-10	背胶改为 1.0mm PE 泡棉; 盖板增加镀 AF; 变更 LCD/TP FPC 导电双面胶位置与尺寸; 变更保护膜上层手撕位位置; 变更二维码贴附位置;TP 排线增加露铜 , 更改倒角尺寸 .TP/LCD 排线弯折尺寸缩短 0.4MM	FLQ
V03	2025-01-10	背光元件槽改成封闭,排线弯折区加绿油, 排线测试点加绝缘胶	FLQ

2 GENERAL INFORMATION

The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD. 3

Item	Specification	Unit
LCD size 液晶面板尺寸	3.97	inch
Display Mode 显示模式	Normally Black	--
Resolution 分辨率	480(RGB)x800	Pixel
Pixel pitch 像素尺寸	0.108(H) x 0.108(V)	mm
Pixel Arrangement 像素排列	RGB Vertical Stripe	
Viewing direction 视角	Free	-
Module outline dimension	61.6(H)*100.9 (V)*3.57(D)	mm
LCD AA 液晶显示区域	51.84 (H)* 86.4 (V)	mm
TP VA 触摸可视区域	52.44 (H)* 87.0 (V)	mm
Colors 颜色深度	16.7M	-
Driver IC 驱动芯片	ST7701SN	-
Interface 接口类型	MIPI	--
Backlight 背光类型	White LED	--
Touch IC 触摸芯片	CHSC6540	--
Surface hardness 表面硬度	6H	--
支持点数	分区两点	--
Touch structure 触摸结构	G+F	--
Seat mode 贴合方式	框贴	--
Operating Temperature 工作温度	-20℃~ +70℃	--
Storage Temperature 存储温度	-30℃~ +80℃	--

3 ABSOLUTE MAXIMUM RATINGS

The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD.

Parameter	Symbol	Min	Max	Unit	Note
Power Supply voltage 1	VCI~GND	-0.3	+5.1	V	
Power Supply voltage 2	IOVCC~GND	-0.3	+5.1	V	
Logic Input Voltage Range	V _{IN}	-0.3	IOVCC+0.5	V	
Logic Output Voltage Range	V _O	-0.3	IOVCC+0.5	V	
Operating temperature	Topr	-20	+70	°C	
Storage temperature	Tstg	-30	+80	°C	

* The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

4 DC ELECTRICAL CHARACTERISTICS

4.1 Driving TFT LCD Panel

AGND = GND = 0V, Ta = 25°C

Parameter	Symbol	Min	Typ	Max	Unit
Supply voltage for analog circuit	VCI	2.5	2.8	3.6	V
Supply voltage for logic circuit	IOVCC	1.65	1.8	3.3	V
Input voltage 'H'level	V _{IH}	0.7*IOVCC	—	IOVCC	V
Input voltage 'L'level	V _{IL}	GND	—	0.3*IOVCC	V
Output voltage 'H'level	V _{OH}	0.8*IOVCC	—	IOVCC	V
Output voltage 'L'level	V _{OL}	GND	—	0.2*IOVCC	V

4.2 Backlight Characteristics

Ta = 25°C

Item	Symbol	Min	Typ	Max	Unit	Condition
Forward voltage	V _f	11.2	12.8	13.2	V	If=40mA
Luminance	LV	260	290	-	cd/m ²	
Number of LED	-	4X2			Piece	-
Connection mode	S/P	4Serial/4Parallel			-	-

Using condition: constant current driving method If=2* 20mA (+/-10%)

5 TIMING CHARACTERISTICS

5.1 Serial Interface Characteristics(3-line serial)




Figure 5.1 3-line serial Interface Timing Characteristics

$T_a=25^{\circ}\text{C}$, $\text{IOVCC}=1.65\sim 3.7\text{V}$, $\text{VCC}=2.5\sim 3.7\text{V}$

Signal	Symbol	Parameter	Min	Max	Unit	Description
CSX	T_{CSS}	Chip select setup time(write)	15	-	ns	
	T_{CSH}	Chip select hold time(write)	15	-	ns	
	T_{CSS}	Chip select setup time(read)	60	-	ns	
	T_{SCC}	Chip Select hold time(read)	60	-	ns	
	T_{CHW}	Chip Select 'H' pulse width	40	-	ns	
SCL	T_{SCYCW}	Serial clock cycle(write)	66	-	ns	Write Command & Data Ram
	T_{SHW}	SCL 'H' pulse width(write)	15	-	ns	
	T_{SLW}	SCL 'L' pulse width(write)	15	-	ns	
	T_{SCYCR}	Serial clock cycle(read)	150	-	ns	Read Command & Data Ram
	T_{SHR}	SCL 'H' pulse width(read)	60	-	ns	
	T_{SLR}	SCL 'L' pulse width(read)	60	-	ns	
SDA (DIN)	T_{SDS}	Data setup time	10	-	ns	
	T_{SDH}	Data hold time	10	-	ns	

Note : The rising time and falling time (T_r , T_f) of input signal are specified at 15 ns or less. Logic high and low levels are specified as 30% and 70% of IOVCC for Input signals.

Table 5.1 3-line Serial Interface Characteristics

5.2 RGB Interface Characteristics




Figure 5.2.1 RGB Interface Timing Characteristics


$T_a=25^{\circ}\text{C}$, $\text{IOVCC}=1.8\text{V}$, $\text{VCC}=2.8\text{V}$

Signal	Symbol	Parameter	Min	Max	Unit	Description
HSYNC, VSYNC	T_{SYNCS}	VSYNC,HSYNV Setup Time	5	-	ns	
ENABLE	T_{ENS}	Enable setup time	5	-	ns	
	T_{ENH}	Enable hold time	5	-	ns	
DOTCLK	PWDH	DOTCLK High-level Pulse Width	15	-	ns	
	PWDL	DOTCLK Low-level Pulse Width	15	-	ns	
	T_{CYCD}	DOTCLK Cycle Time	33	-	ns	
	T_{rghr} , T_{rghf}	DOTCLK Rise/Fall time.	-	15	ns	
DB	T_{PDS}	PD Data Setup Time	5	-	ns	
	T_{PDH}	PD Data Hold Time	5	-	ns	

Table 5.2.2 18/16 Bits RGB Interface Timing Characteristics

6. Reset Timing

The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD.



Signal	Symbol	Parameter	Min.	Max.	Unit
RESX	t_{RW}	Reset pulse duration	10(Note)	-	us
	t_{RT}	Reset cancel	-	10(Note)	ms
			-	120(Note)	ms

Notes:

1. The reset cancel also includes required time for loading ID bytes, VCOM setting and other settings from EEPROM (or similar device) to registers.

This loading is done every time when there is HW reset cancel time (t_{RT}) within 10 ms after a rising edge of RESX.


2. Spike due to an electrostatic discharge on RESX line does not cause irregular system reset according to the table below :

RESX Pulse	Action
Shorter than 5us	Reset Rejected
Longer than 9us	Reset
Between 5us and 9us	Reset starts

3. During the Resetting period, the display will be blanked(The display is entering blanking sequence, which maximum time is 120 ms, when Reset


Starts at Sleep-Out status. The display remains the blank state in Sleep-In mode). Then return to Default condition for Hardware Reset

4. Spike Rejection also applies during a valid reset pulse as shown below :



5. When Reset applied during Sleep-In Mode.
6. When Reset applied during Sleep-Out Mode
7. It is necessary to wait 10ms after releasing RESX before sending commands. Also Sleep Out command cannot be sent for 120 ms.

7-2 EXTERNAL DIMENSIONS



The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD.

1	TP_VDD3V3	VDD pin for CTP
2	GND	Power ground
3	TP_INT(3.3V)	INT pin for CTP
4	TE	Tearing Effect Output Pin.
5	TP_SDA(3.3V)	SDA pin for CTP
6	GND	Power ground
7	TP_SCL(3.3V)	SCL pin for CTP
8	LCD_RESET	Reset signal(low active)
9~10	GND	Power ground
11	TP_RST(3.3V)	RST pin for CTP
12	NC	NC
13	LEDA	LED backlight anode
14	NC	NC
15	LEDA	LED backlight anode
16	GND	Power ground
17	LEDK	LED backlight cathode
18	NC	NC
19	LEDK	LED backlight cathode
20	NC	NC
21~22	GND	Power ground
23	LCD_VDD1V8	Power supply for the logic power and I/O circuit.
24	CLK_P	MIPI-DSI data lane positive input pin
25	LCD_VDD1V8	Power supply for the logic power and I/O circuit.
26	CLK_N	MIPI-DSI data lane negative input pin
27	LCD_VDD2V8	Power supply for the analog power
28	GND	Power ground
29	LCD_VDD2V8	Power supply for the analog power
30	LAN1_P	DSI data lane 1 positive input pin
31	GND	Power ground
32	LAN1_N	DSI data lane 1 negative input pin
33	TAMPER_N0_1	Short to tp pin
34	GND	Power ground
35	NC	NC
36	LAN0_P	DSI data lane 0 positive input pin
37	TAMPER_N3	Short to tp pin
38	LAN0_N	DSI data lane 0 negative input pin
39	GND	Power ground
40	GND	Power ground


9 ELECTRO-OPTICAL CHARACTERISTICS

Item	Symbol	Condition	Min	Typ	Max	Unit	Note
Transmittance (w/o polarizer)	T%	$\theta=0^\circ$ $T_a=25^\circ\text{C}$	-	4.14	-	%	1
Contrast ratio	Cr		720	900	-	-	3
Response time	$T_{on}+T_{off}$		-	20	25	ms	4
TLCM Luminance	LV		260	290	-	cd/m^2	2
Color Gamut	%		-	70	-	%	
Viewing angle range	H or V er	Θ_{x+}	-	80	-	deg	5
		Θ_{x-}	-	80	-	deg	
		Θ_{y+}	-	80	-	deg	
		Θ_{y-}	-	80	-	deg	
CIE(x,y) chromaticity	Red	x	-0.03	0.628	+0.03	-	6
		y		0.376		-	
	Green	x		0.341		-	
		y		0.606		-	
	Blue	x		0.139		-	
		y		0.052		-	
	White	x		0.30		-	
		y		0.32		-	

Note 1.Ambient condition: $25^\circ\text{C}\pm 2^\circ\text{C}$, $60\pm 10\%\text{RH}$, under 10 Lux in the darkroom。

Note 2.Measure device: BM-7A (TOPCON), viewing cone= 2°


Lv = Average Surface Luminance with all white pixels (P1,P2,P3,P4,P5)




Note 3. Definition of Contrast Ratio:

$$CR = \frac{\text{Average Surface Luminance with all black pixels (P1,P2,P3,P4,P5)}}{\text{Average Surface Luminance with all white pixels (P1,P2,P3,P4,P5)}}$$


Note 4. Definition of Response Time (T_{on} , T_{off}), The response time is defined as the time interval between the 10% and 90% amplitudes.



Note 5. Definition of view angle(θ , ψ):



Note 6. The LCD module should be stabilized at a given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 20 minutes in a windless room. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE(x,y) chromaticity.



Light spot size $\varnothing = 7\text{mm}$, 500mm distance from the LCD surface to detector lens
measurement instrument is TOPCON's luminance meter BM-7

10. RELIABILITY TEST

Reliability test conditions (Polarizer characteristics null)

No.	Items	Condition	Inspection after test
1	High Temperature Storage	T = 80℃for 96 hr	Inspection after 4 hours storage at room temperature, the sample shall be free from defects: 1.Air bubble in the LCD 2.Sealleak; 3.Non-display; 4.missing segments; 5.Glass crack; 6.Current Idd is twice higher than initial value.
2	Low Temperature Storage	T = -30℃for 96 hr	
3	High Temperature Operating	T = 70℃for 96 hr	
4	Low Temperature Operating	T = -20℃for 96 hr (But no condensation of dew)	
5	High Temp. and High Humidity Storage	T = 60℃/90% for 96 hr (But no condensation dew)	
6	Thermal Shock	-20℃~25~70℃×10cycles (30min.) (5min.) (30min.)	
7	Packing Vibration (non-operation)	Frequency: 10Hz~55Hz~10Hz Amplitude: 1.0mm, X, Y, Z direction for total 3hours (Packing condition)	
8	ESD	Contact:±4KV,Air: ±6KV R: 330Ω C: 150pF Air discharge, 10time	

Note:

- (1)The test samples should be applied to only one test item.
- (2)Sample size for each test item is 5~10pcs.
- (3)In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judge as a good part.
 Using ionizer(an antistatic blower) is recommended at working area in order to reduce electro-static voltage.
 When removing protection film from LCM panel, peel off the tag slowly (recommended more than one second) while blowing with ionizer toward the peeling face to minimize ESD which may damage electrical circuit.
- (4) Please use automatic switch testing mode when test operating mode.

11 📊 INSPECTION CRITERION

This specification is made to be used as the standard acceptance/rejection criteria for

The information contained herein is the exclusive property of ShenZhen BELIJ Electronic technology co., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ShenZhen BELIJ Electronic technology co., LTD.

Normal LCM Product.

1 Sample plan

Sampling plan according to GB/T2828.1-2003/ISO 2859-1: 1999 and ANSI/ASQC Z1.4-1993,normal level 2 and based on:


Major defect: AQL 0.65

Minor defect: AQL 1.0

2. Inspection condition

Viewing distance for cosmetic inspection is about 30cm with bare eyes, and under an environment of 20~40W light intensity, all directions for inspecting the sample should be within 45° against perpendicular line. (Normal temperature 20~25°C and normal humidity 60±15%RH).

3. Definition of inspection zone in LCD.



Zone A: character/Digit area

Zone B: viewing area except Zone A (Zone A + Zone B=minimum Viewing area)

Zone C: Outside viewing area (invisible area after assembly in customer's product)

Fig.1 Inspection zones in an LCD.

Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble for quality and assembly of customer's product.


4.Standards of inspection items

4.1 Major Defect


Item No	Items to be inspected	Inspection Standard	Classification of defects
4.1.1	All functional defects	1.No display	Major
		2.Display abnormally	
		3.Missing vertical, horizontal segment	
		4.Short circuit	
		5. Back-light no lighting, flickering and abnormal lighting.	
4.1.2	Missing	Missing component	
4.1.3	Outline dimension	Overall outline dimension beyond the drawing is not allowed.	

4.1.4	linearity	No more than 1.5%	
-------	-----------	-------------------	--

4.2 Cosmetic Defect





Item No	Items to be inspected	Inspection Standard				Classification of defects
4.2.1	Clear Spots Black and white Spot defect Pinhole, Foreign Particle, polarizer Dirt	For dark/white spot, size Φ is defined as $\Phi = (x + y)/2$				Minor
		1				
		Zone	Acceptable Qty			
			A	B	C	
		Size(mm)	Ignore			
		$\Phi \leq 0.15$				
		$0.15 < \Phi \leq 0.20$				
		$0.20 < \Phi \leq 0.30$				
		$\Phi > 0.30$				
	Clear Spots TP Dirt	2				Minor
		Zone	Acceptable Qty			
			A	B	C	
		Size(mm)	Ignore			
		$\Phi \leq 0.15$				
		$0.15 < \Phi \leq 0.20$				
		$0.20 < \Phi \leq 0.30$				
		$\Phi > 0.30$				
	Dim Spots Circle shaped and dim edged defects	3				Minor
		Zone	Acceptable Qty			
			A	B	C	
		Size(mm)	Ignore			
		$\Phi \leq 0.2$				
		$0.20 < \Phi \leq 0.40$				
		$0.40 < \Phi \leq 0.60$				
		$\Phi > 0.60$				

Item No	Items to be inspected	Inspection Standard			Classification of defects
4.2.2	Line defect	Size(mm)		Acceptable Qty	Minor
		L(Length)	W(Width)	Zone	



	Black line, White line, Foreign material on polarizer			A	B	C	Ignore	
		Ignore	W≤0.05	Ignore				
		L ≤5.0	0.05<W≤0.08	2				
			W>0.08	0				
	Foreign material on TP film	The line can be seen after mobile phone in the operating condition:						Minor
		Size(mm)		Acceptable Qty				
		L(Length)	W(Width)	Zone				
				A	B	C		
		Ignore	W≤0.05	Ignore			Ignore	
		L ≤5.0	0.05<W≤0.08	3				
			W>0.08	0				
4.2.3	Dim line defect Polarizer scratch TP film scratch	If the scratch can be seen after mobile phone cover assembling or in the operating condition, judge by the line defect of 4.2.2. If the scratch can be seen only in non-operating condition or some special angle, judge by the following.						Minor
		Size(mm)		Acceptable Qty				
		L(Length)	W(Width)	Zone				
				A	B	C		
		Ignore	W≤0.03	Ignore			Ignore	
		5.0< L≤10.0	0.03<W≤0.05	2				
		L≤5.0	0.05<W≤0.08	1				
			W>0.08	0				
4.2.4	Polarize Air bubble	Air bubbles between glass & polarizer						Minor
		Zone Size(mm)		Acceptable Qty				
				A	B	C		
		Φ≤0.20		Ignore			Ignore	
		0.20<Φ≤0.3		2				
		Φ>0.30		0				

Item No	Items to be inspected	Inspection Standard	Classification of defects
---------	-----------------------	---------------------	---------------------------

4.35	Glass defect	(i) Chips on corner A:LCD Glass defect 	Minor						
		<table><tr><th>X(mm)</th><th>Y(mm)</th><th>Z(mm)</th></tr><tr><td>≤3.0</td><td>≤3.0</td><td>Disregard</td></tr></table>		X(mm)	Y(mm)	Z(mm)	≤3.0	≤3.0	Disregard
		X(mm)		Y(mm)	Z(mm)				
		≤3.0		≤3.0	Disregard				
		Notes: S=contact pad length Chips on the corner of terminal shall not be allowed to extend into the ITO pad or expose perimeter seal. B:TP Glass defect 							
		<table><tr><th>X(mm)</th><th>Y(mm)</th><th>Z(mm)</th></tr><tr><td>≤3.0</td><td>≤3.0</td><td>Disregard</td></tr></table>		X(mm)	Y(mm)	Z(mm)	≤3.0	≤3.0	Disregard
		X(mm)		Y(mm)	Z(mm)				
		≤3.0		≤3.0	Disregard				
		(ii) Usual surface cracks A:LCD Glass defect 							
		<table><tr><th>X(mm)</th><th>Y(mm)</th><th>Z(mm)</th></tr><tr><td>≤3.0</td><td><Inner border line of the seal</td><td>Disregard</td></tr></table>		X(mm)	Y(mm)	Z(mm)	≤3.0	<Inner border line of the seal	Disregard
X(mm)	Y(mm)	Z(mm)							
≤3.0	<Inner border line of the seal	Disregard							
B:TP Glass defect 									
<table><tr><th>X(mm)</th><th>Y(mm)</th><th>Z(mm)</th></tr><tr><td>≤6.0</td><td><2.0</td><td>Disregard</td></tr></table>	X(mm)	Y(mm)	Z(mm)	≤6.0	<2.0	Disregard			
X(mm)	Y(mm)	Z(mm)							
≤6.0	<2.0	Disregard							
(iii) Crack Cracks tend to break are not allowed. 									

12 PRECAUTIONS FOR USE OF LCD MODULES

1. Handling Precautions

- (1) The display panel is made of glass and polarizer. As glass is fragile. It tends to become or chipped during handling especially on the edges. Please avoid dropping or jarring. Do not subject it to a mechanical shock by dropping it or impact.
- (2) If the display panel is damaged and the liquid crystal substance leaks out, be sure not to get any in your mouth. If the substance contacts your skin or clothes, wash it off using soap and water.
- (3) Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary. Do not touch the display with bare hands. This will stain the display area and degraded insulation between terminals (some cosmetics are determined to the polarizer).
- (4) The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully. Do not touch, push or rub the exposed polarizers with anything harder than an HB pencil lead (glass, tweezers, etc.). Do not put or attach anything on the display area to avoid leaving marks on. Condensation on the surface and contact with terminals due to cold will damage, stain or dirty the polarizer. After products are tested at low temperature they must be warmed up in a container before coming is contacting with room temperature air.
- (5) If the display surface becomes contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If it is heavily contaminated, moisten cloth with one of the following solvents
 - Isopropyl alcohol
 - Ethyl alcoholDo not scrub hard to avoid damaging the display surface.
- (6) Solvents other than those above-mentioned may damage the polarizer. Especially, do not use the following.
 - Water
 - Ketone
 - Aromatic solventsWipe off saliva or water drops immediately, contact with water over a long period of time may cause deformation or color fading. Avoid contacting oil and fats.
- (7) Exercise care to minimize corrosion of the electrode. Corrosion of the electrodes is accelerated by water droplets, moisture condensation or a current flow in a high-humidity environment.
- (8) Install the LCD Module by using the mounting holes. When mounting the LCD module make sure it is free of twisting, warping and distortion. In particular, do not forcibly pull or bend the I/O cable or the backlight cable.
- (9) Do not attempt to disassemble or process the LCD module.
- (10) NC terminal should be open. Do not connect anything.
- (11) If the logic circuit power is off, do not apply the input signals.
- (12) Electro-Static Discharge Control, Since this module uses a CMOS LSI, the same careful attention should be paid to electrostatic discharge as for an ordinary CMOS IC. To prevent destruction of

the elements by static electricity, be careful to maintain an optimum work environment.

- Before remove LCM from its packing case or incorporating it into a set, be sure the module and your body have the same electric potential. Be sure to ground the body when handling the LCD modules.
- Tools required for assembling, such as soldering irons, must be properly grounded. Make certain the AC power source for the soldering iron does not leak. When using an electric screwdriver to attach LCM, the screwdriver should be of ground potentiality to minimize as much as possible any transmission of electromagnetic waves produced sparks coming from the commutator of the motor.
- To reduce the amount of static electricity generated, do not conduct assembling and other work under dry conditions. To reduce the generation of static electricity be careful that the air in the work is not too dried. A relative humidity of 50%-60% is recommended. As far as possible make the electric potential of your work clothes and that of the work bench the ground potential
- The LCD module is coated with a film to protect the display surface. Exercise care when peeling off this protective film since static electricity may be generated

(13) Since LCM has been assembled and adjusted with a high degree of precision, avoid applying excessive shocks to the module or making any alterations or modifications to it.

- Do not alter, modify or change the shape of the tab on the metal frame.
- Do not make extra holes on the printed circuit board, modify its shape or change the positions of components to be attached.
- Do not damage or modify the pattern writing on the printed circuit board.
- Absolutely do not modify the zebra rubber strip (conductive rubber) or heat seal connector.
- Except for soldering the interface, do not make any alterations or modifications with a soldering iron.
- Do not drop, bend or twist LCM.

2. Storage precautions

2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ~ 40℃ Relatively humidity: ≤80%

2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

2.4 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

----- END